

From the INTERNATIONAL BUREAU

**PCT**NOTIFICATION CONCERNING  
SUBMISSION OR TRANSMITTAL  
OF PRIORITY DOCUMENT

(PCT Administrative Instructions, Section 411)

To:

Att: POULSEN, Henning Knak  
Oticon A/S  
Strandvejen 58  
DK-2900 Hellerup  
DANEMARK

|  |   |
|--|---|
| Date of mailing (day/month/year)<br>17 March 2005 (17.03.2005) |   |
| Applicant's or agent's file reference<br>P-2004-001WO          | <b>IMPORTANT NOTIFICATION</b>   |
| International application No.<br>PCT/DK05/000100               | International filing date (day/month/year)<br>16 February 2005 (16.02.2005) |
| International publication date (day/month/year)                | Priority date (day/month/year)<br>19 February 2004 (19.02.2004)             |
| Applicant<br>OTICON A/S et al                                  |   |

1. By means of this Form, which replaces any previously issued notification concerning submission or transmittal of priority documents, the applicant is hereby notified of the date of receipt by the International Bureau of the priority document(s) relating to all earlier application(s) whose priority is claimed. Unless otherwise indicated by the letters "NR", in the right-hand column or by an asterisk appearing next to a date of receipt, the priority document concerned was submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b).
2. *(If applicable)* The letters "NR" appearing in the right-hand column denote a priority document which, **on the date of mailing of this Form, had not yet been received by the International Bureau** under Rule 17.1(a) or (b). Where, under Rule 17.1(a), the priority document must be submitted by the applicant to the receiving Office or the International Bureau, but the applicant fails to submit the priority document within the applicable time limit under that Rule, **the attention of the applicant is directed** to Rule 17.1(c) which provides that no designated Office may disregard the priority claim concerned before giving the applicant an opportunity, upon entry into the national phase, to furnish the priority document within a time limit which is reasonable under the circumstances.
3. *(If applicable)* An asterisk (\*) appearing next to a date of receipt, in the right-hand column, denotes a priority document **submitted or transmitted to the International Bureau but not in compliance with Rule 17.1(a) or (b)** (the priority document was received after the time limit prescribed in Rule 17.1(a) or the request to prepare and transmit the priority document was submitted to the receiving Office after the applicable time limit under Rule 17.1(b)). Even though the priority document was not furnished in compliance with Rule 17.1(a) or (b), the International Bureau will nevertheless transmit a copy of the document to the designated Offices, for their consideration. In case such a copy is not accepted by the designated Office as the priority document, Rule 17.1(c) provides that no designated Office may disregard the priority claim concerned before giving the applicant an opportunity, upon entry into the national phase, to furnish the priority document within a time limit which is reasonable under the circumstances.

| <u>Priority date</u>          | <u>Priority application No.</u> | <u>Country or regional Office<br/>or PCT receiving Office</u> | <u>Date of receipt<br/>of priority document</u> |
|-------------------------------|---------------------------------|---|---|
| 19 February 2004 (19.02.2004) | PA 2004<br>00259                | DK  | 07 March 2005 (07.03.2005)                      |

|   |   |
|---|---|
| The International Bureau of WIPO<br>34, chemin des Colombettes<br>1211 Geneva 20, Switzerland | Authorized officer<br><br>Olaiz Alicia                          |
| Facsimile No. +41 22 740 14 35  | Facsimile No. +41 22 338 71 30<br>Telephone No. +41 22 338 9288 |

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/DK05/000100

International filing date: 16 February 2005 (16.02.2005)

Document type: Certified copy of priority document

Document details: Country/Office: DK  
Number: PA 2004 00259  
Filing date: 19 February 2004 (19.02.2004)

Date of receipt at the International Bureau: 07 March 2005 (07.03.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse




# Kongeriget Danmark

Patent application No.: PA 2004 00259  
Date of filing: 19 February 2004  
Applicant: Oticon A/S  
(Name and address) Strandvejen 58  
DK-2900 Hellerup  
Denmark

Title: Hearing aid with antenna for reception and transmission of electromagnetic signals  
Høreapparat med antenne til brug for modtagelse og transmission af elektromagnetiske signaler

IPC: H 04 R 25/00

This is to certify that the attached documents are exact copies of the above mentioned patent application as originally filed.



**Patent- og Varemærkestyrelsen**  
Økonomi- og Erhvervsministeriet

01 March 2005

  
Susanne Morsing

## TITLE

Hearing aid with antenna for reception and transmission of electromagnetic signals.

## AREA OF THE INVENTION

5

The invention regards hearing aids or other listening devices wherein wireless reception and transmission means are provided. Especially in ITE (in the ear) and CIC (completely in the canal) style hearing aids it is a problem to accommodate antennas for the provision of the wireless transmission.

10

## BACKGROUND OF THE INVENTION

In small hearing aids which are to be worn in the ear, the distance between the antenna and the receiver or speaker will be small and as a result, the antenna is likely to pick up  
15 unwanted electromagnetic radiation. Inside the hearing aid a microphone and a receiver are placed along with a signal processing device and a battery. The receiver delivers a signal to the user which is perceivable as sound but at the same time the receiver will radiate electromagnetic energy and this is likely to be collected by the antenna and may give rise to either feedback problems or noise. Hearing aids of the above kind are often  
20 custom made and the location of electronic devices (the receiver and the signal processing device) within the casing may differ in different hearing aids. As the function of the antenna may depend on the location of nearby electric components it is a problem to not know the exact location of nearby components in advance as this may lead to antennas with widely varying performance in different hearing aids.

25

Today wireless communication at frequencies above approximately 1 MHz is not implemented in In-The-Ear (ITE) hearing aids. This will most likely change in the future, and then highly efficient antennas (compared to the available volume) will be needed in order to enable acceptable performance (range, current consumption, etc.). One patent  
30 application has been published in this area covering amongst others the use of the pull-out string as an antenna. US patent 5721783 discloses a hearing aid or audio communication system includes an earpiece that can be hidden in the ear canal, and which communicates wirelessly with a remote processor unit, that enhances audio

signals and can be concealed under clothing. The disclosed hearing aid has an antenna arranged in conjunction with the pull out string of the hearing aid.

5 In prior art document EP 1326302 an integrated circuit fractal antenna in a hearing aid device is disclosed. The fractal antenna can be incorporated in the hearing device to optimize wireless communication capabilities of the device.

EP 1013143 discloses a hearing aid comprising a detector for wireless reception of signals and a system comprising said hearing aid. The disclosed hearing aid  
10 accommodates an electronic circuit and a battery compartment. A faceplate includes a lid-shaped element which can be moved with respect to the battery compartment. A detector is secured to the lid-shaped element, which detector is embodied so as to be suitable for the wireless reception of signals and conversion thereof to electrical signals. The hearing aid is provided with an electrical connection means which, at least in the  
15 closed position of the lid-shaped element, connects the detector to the electronic circuit. The disclosed detector is used for the reception of signals in the infrared light range. As this known receptor works in the infrared light range, where the penetration depth of the signals is poor, it must be placed at an external surface part.

20 The antenna according to the present invention will be working in the radio frequency range, where the penetration depth of signals is grater, and it cannot in advance easily be determined what will be an advantageous position of the antenna. Further the sensitivity of a radio frequency antenna towards close by electronic components is a problem which has not been dealt with previously.

25

### SUMMARY OF THE INVENTION

It is the object of the invention to provide an antenna for wireless transmission/reception of electromagnetic signals in an ITE or CIC style hearing aid or other listening device,  
30 wherein the antenna is not influenced by the varying position of the receiver or other electronic components of the listening device. Further an improved and uniform radiation and reception characteristic for custom made hearing aids is desired.

This is achieved by the communication device as claimed in claim 1. Accordingly the device is adapted for placement in a users ear and comprises a shell part enclosing an input transducer for receiving an input signal, a signal processing device and an output transducer for providing a signal perceivable as sound, a battery located at a surface part  
5 of the shell which is facing away from the head of the user, a transmission and reception circuit for transmission and reception of electromagnetic energy, and whereby an antenna for radiating and/or receiving electromagnetic energy is provided such that it has a first surface turned towards the surroundings and a second surface located in close proximity of the battery.

10

By placing the antenna outwardly of the battery the battery may be used as ground, and this is an advantage. Also the position of the battery between the antenna and the other components within the hearing aid will help to ensure, that the antenna does not become de-tuned when the receiver or other components within the shell are fixed at a given  
15 position during finishing of custom made hearing aids. Further the battery will provide electromagnetic shielding between the antenna and other parts of the hearing aid circuitry.

According to the invention the antenna is tuned to radiate and/or receive electromagnetic  
20 energy in the frequency range of 50 MHz to 50 GHz. Within this range radio communication is allowed in various bands in most countries without any licence. Examples of such bands are the ISM bands. This also means that there is likely to be some noise in these frequency bands, and this is a further reason for the antenna to be effective. The antenna is usable for either digital or analog coding of signals.

25

Preferably the antenna is shaped as a part of a flexprint. This construction is advantageous because it is possible to use the flexibility of the flexprint to pride connections across possible moving parts, like from the battery lid to the rest of the hearing aid.

30

In an embodiment of the invention the antenna is embedded in material externally of the battery. Embedding the antenna in material will aid to protect the antenna and at the same time minimize the space taken up by the antenna. The embedding may be

accomplished by over-molding a flexprint-antenna or a solid metal part. It could also be realized by providing a surface metalization trace on a polymer part of the antenna and then overmolding or covering the surface trace in some other way.

In a further embodiment the antenna covers a surface area of the shell which is wider  
5 than the projection of the battery onto the faceplate surface. In most ITE hearing aids the battery lid has the same dimensions as the battery. This is a serious limitation for the antenna, and this can be overcome by allowing the antenna to extend sideways beyond the size of the battery and the battery lid. The antenna cannot however be allowed to extend beyond the overall size of the hearing aid.

10

In an embodiment the antenna comprises a loop, which is usable also as a charging loop for a battery. In modern hearing aids rechargeable batteries are becoming more common, and in order to charge the batteries the hearing aid is placed in a strong varying magnetic field, which will generate a current in an electric loop or coil inside the hearing aid. It  
15 has been discovered that the antenna can be used as the induction loop on the secondary side of such a charging device.

#### BRIEF DESCRIPTION OF THE DRAWINGS

- 20 Fig. 1 is a side view of a schematic representation of an ITE hearing aid with an antenna according to the invention,  
Fig. 2 is a schematic representation of an antenna according to the invention,  
Fig. 3 is a schematic representation of an antenna according to the invention,  
Fig. 4 is a schematic representation of an antenna according to the invention,  
25 Fig. 5 is a schematic representation of an antenna in side sectional view,  
Fig. 6 is a schematic representation of an antenna in side sectional view.

#### DESCRIPTION OF A PREFERRED EMBODIMENT

- 30 Initially it is worth noting that we are dealing with small antennas, meaning that the wavelength is much larger than the physical size of the antenna and therefore the antenna has a narrow bandwidth (high quality factors) and low efficiency (small radiation resistance compared to the loss resistance). If high currents are dominating, the structure

will mainly radiate the magnetic field and vice versa: if high voltages are present, a dominating electric field must be expected.

In fig. 1 a schematic sectional representation of a CIC hearing aid is shown with an antenna according to the invention. The hearing aid comprises a custom made shell part 2 which is placed deep in the ear canal. Instead of being custom made the shell part can be either flexible or have a flexible outer portion which allows it to be inserted into the ear. 1 is an outline of the external ear of a person. The shell part 2 encloses a receiver 5, a signal processing unit 4 and a microphone 3. The receiver 5 is arranged with an output orifice (not shown) close to the tympanic membrane 6 in order to deliver a useful audio signal to the user. A front plate part 12 is arranged to face the surroundings. In this part a battery drawer 7 with a battery 8 is placed. Also an extractor 9 may be comprised in the front plate. Other components may be placed in the shell or associated with the front plate part 12, such as further microphones or connectors for wired contact with other equipment like telephones. Also the hearing aid will comprise a transmission and/or reception circuit in order to feed/receive electromagnetic energy to/from the antenna. This circuit is connected to the antenna and to the signal processing part 4. The transmission and/or reception circuit is not shown in the figures, and it may be configured as an independent circuit part or it can be configured as part of the signal processing part 4.

An antenna 10 is schematically shown. The antenna 10 is placed in the area between the battery and the external surface of the frontal plate. The antenna 10 is preferably associated the battery drawer 7.

25

Fig. 2 displays a loop antenna 13. The inductive part of the antenna impedance has to be resonated with an external capacitor (not shown). The magnetic field generated by the loop current is the radiating component and dominating in the near field, especially if it is excited by a balanced signal. If operated in unbalanced mode it will also radiate the electric field. The antenna is less sensitive to detuning from near by objects. The loop has two connections 16 and 11 and can be placed circumferentially with regards to the battery 8.

30

In fig. 3 a schematic representation of a loop + helix antenna is shown. This antenna structure is unbalanced and can be made resonant by itself or in combination with an external capacitor. The antenna impedance is adjustable by tapping. Both the H and E fields are radiated from the structure and due to the high end impedance of the helix and compared to the loop antenna, increased sensitivity towards detuning by near by objects must be expected. Two connection points 14 and 15 are shown. A loop of two turns and a helix part of two turns is showed but a higher or lower number of turns may be used.

Fig. 4 discloses a patch antenna 17. Because of the small size of the patch 17 compared to the wavelength the patch 17 can be considered as a capacitor that will require an inductor to be made resonant. The duality between the small loop and the patch is evident. The patch will radiate the electric field from the edges but the tuning inductor will inevitably also add to the radiation pattern with a magnetic contribution. If the patch has a nearby ground plane, only moderate sensitivity to detuning from close by objects will occur.

In fig. 5 an enlarged side sectional view of an embodiment of the invention is schematically shown. The antenna 10 could be either a loop or a patch antenna and in the shown embodiment it is embedded within the material of the battery lid 2. In this way the antenna 10 will lie close to the battery 8, which thereby may function as ground plane and at the same time shield the antenna 10 from receiving radiation from the possible electromagnetic noise from the speaker or other electronic objects in the hearing aid.

In fig. 6, an other embodiment of the invention is schematically shown in sectional view. Here the antenna 10 has an extension, which is wider than the projection of the battery 8 on the battery lid 7. The shielding effect of the battery 10 and also the usefulness of the battery as ground plane are not impaired by this, and at the same time an antenna covering a larger area is achieved, whereby further the antenna becomes more effective.

5

## CLAIMS

1. Communication device which is adapted for placement in a users ear and comprises a shell part enclosing an input transducer for receiving an input signal, a signal processing device and an output transducer for providing a signal perceivable as sound, a battery located at a surface part of the shell which is facing away from the head of the user, a transmission and reception circuit for transmission and/or reception of electromagnetic energy, and whereby an antenna for radiating and/or receiving electromagnetic energy is provided such that it has a first surface turned towards the surroundings and a second surface located in close proximity of the battery.
2. Communication device as claimed in claim 1, wherein the antenna is tuned to radiate and/or receive electromagnetic energy in the frequency range of 50 MHz to 50 GHz.
3. Communication device as claimed in claim 1, wherein the antenna is shaped as a part of a flexprint.
4. Communication device as claimed in claim 1, wherein the antenna is embedded in material externally of the battery.
5. Communication device as claimed in claim 4, wherein the antenna is a metal part.
6. Communication device as claimed in claim 1, wherein the antenna is manufactured by deposition of metal material on surface parts of the faceplate and/or battery drawer.
7. Communication device as claimed in claim 1, wherein the antenna covers a surface area of the shell which is wider than the projection of the battery onto the faceplate surface.

8. Communication device as claimed in claim 1, wherein the antenna comprises a loop, which is usable also as a charging loop for a battery.

## ABSTRACT

The invention regards a communication device which is adapted for placement in a users ear. The communication device comprises a shell part enclosing an input transducer for  
5 receiving an input signal, a signal processing device and an output transducer for providing a signal perceivable as sound, a battery located at a surface part of the shell which is facing away from the head of the user, a transmission and reception circuit for transmission and/or reception of electromagnetic energy. According to the invention an antenna for radiating and/or receiving electromagnetic energy is provided such that it has  
10 a first surface turned towards the surroundings and a second surface located in close proximity of the battery.

15 Fig. 1

Modtaget

19 FEB. 2001

PVS

1/6




Fig. 1




Fig. 2





Fig. 3

17



PATCH

Fig. 4

5/6




Fig. 5




Fig. 6